



Model : IT-02M - Series

Weight Indicator Memory



SPECIFICATIONS

Display	6 x Red&Green LED / Graphic LCD	6 x Red&Green LED / Graphic LCD
Memory	1200 Records , 250 codes	1200 Records , 250 codes
Character	TIS17 / KU42	TIS17 / KU42
Power Supply	200-230 VAC, 50 or 60 Hz, 1 A	200-230 VAC, 50 or 60 Hz, 1 A
Signal Input	Analog 1-3 mV/V	Digital Serial RS-485
Excitation Voltage	5 +/- 0.1 VDC	12 +/- 0.5 VDC
Internal Resolution	Upto 1 / 16,777,216	Upto Digital Loadcell
Display increment	999,999 Levels	999,999 Levels
Loadcell	Up to 8 Loadcells	Up to 8 Address
Calibration Method	Software, Storage in EEPROM	Software, Storage in EEPROM
Decimal point	0 – 4 Digits	0 – 4 Digits
Increment Step	1, 2, 5, 10, 20	1, 2, 5, 10, 20
Keyboard	6 KeyPads / PS2 Keyboard	6 KeyPads / PS2 Keyboard
Communication	2 x RS-232C / 1 Parallel	2 x RS-232C / 1 x Parallel
Casing	Stainless Steel	Stainless Steel

Specifications subject to change without notice